



100°C

Water Hose MNG-TRX-100

Specifications

Rubber Tube	Black, non-porous, smooth EPDM inner laye
Reinforcement	Synthetic yarns
Cover	Black, smooth EPDM outer layer, ozone-, weather- and UV-resistant, fabric-patterned from DN 32 upwards
Application	Cold and hot water, soap solutions, as well as most aqueous salt solutions and a large number of chemicals. Up to DN 25 LABS-release agent- and grease-free production.
Temperature	-40°C to +100°C
Rollenlänge	40 m



Only suitable hinged bolt clamps (or clamp jaws) should be used with the MNG-TRX-100 hose. Only these guarantee a secure and durable connection, especially under high pressure. Using other types of clamps can lead to leaks or connection failure.

Description	Ø Inside		Ø Outside	Min. bending radius	Working pressure
	Zoll	mm			
MNG-TRX-100-13	1/2"	13	19,6	50	20
MNG-TRX-100-16	5/8"	16	23,0	60	20
MNG-TRX-100-19	3/4"	19	27,0	65	20
MNG-TRX-100-25	1"	25	34,0	110	20
MNG-TRX-100-32	1 1/4"	32	43,0	170	15
MNG-TRX-100-38	1 1/2"	38	50,0	200	10
MNG-TRX-100-50	2"	50	64,0	300	10

FLEXQ

